

方钻杆旋塞阀 Kelly Valve



方钻杆旋塞阀是钻柱循环系统中的手动控制阀，是防止井喷的有效工具之一。其包括方钻杆上阀和方钻杆下阀分别安置在方钻杆上下两端。用专用扳手按要求转动 90° 即可实现开关。

Kelly cock valve is a manual control valve in the drill string circulation system and is one of the effective tools to prevent blowout . It is upper Kelly valve and lower Kelly valve which is assembled the upper end and lower end of drill pipe. The Kelly valve can be opened on or closed off by the special operating spanner at 90 degrees according to the indicating direction.

规格 Specifications

	型号 Model	外径 OD	内径 ID	连接螺纹	工作压力 WP
上旋塞	XS197	197 (7-3/4)	76.2 (3)	6-5/8REG LH	35MPa 70MPa 105MPa
	XS146	146.1 (5-3/4)	44.4 (1-3/4)	4-1/2REG LH	
下旋塞	XS111	111.1 (4-3/8)	38.1 (1-1/2)	NC31	
	XS121	120.7 (4-3/4)	44.4 (1-3/4)	NC38	
	XS146	146.1 (5-3/4)	44.4 (1-3/4)	4-1/2REG	
	XS165	165.1 (6-1/2)	71.4 (2-13/16)	NC50	
	XS178	177.8 (7)	71.4 (2-13/16)	NC50	
	XS184	184 (7-1/4)	71.4 (2-13/16)	5-1/2FH	

备注：订购或询价时，如需其它尺寸规格，请详细说明。

Note: When ordering or requesting quotation, if size other than above specifications, please specify clearly.