



带正倒划眼稳定器是钻井工程中防止井斜的重要工具，适用于石油、天然气及地质勘探钻井过程中稳定钻具。它以有效的稳定作用增加钻头寿命，提高钻井速度和井身质量。

Special stabilizer with reamers and back-reamers is an important tool in preventing drilling inclination, applying to stabilize oil, gas and geological exploration during drilling. It has an effective stabilizing effect and increases bit life, improves the drilling speed and quality.

规格 Specifications

工作外径 mm (inch) Working O.D	上端螺纹 Up Conn. API	下端螺纹 Down Conn. API	打捞径 Fishing O.D. mm (inch)	打捞径长度 Fishing Neck Length mm (inch)	轴向带宽 Blade Wide mm (inch)	带长 mm (inch) Blade Length	切削齿 数量 Cutter Qty	总长 mm (inch) All length
444.5 (17-1/2)	7-5/8REG	7-5/8REG	229 (9)	700 (27-9/16)	121 (4-3/4)	460 (18-7/64)	18 或 30	2200 (86-39/64)
311 (12-1/4)	6-5/8REG	6-5/8REG	203 (8)	500 (19-11/16)	90 (2-61/64)	460 (18-7/64)	18 或 30	1800 (70-7/8)
215 (8-1/2)	NC50	NC50	165 (6-1/2)	550 (21-21/32)	60 (2-3/8)	460 (18-7/64)	18 或 30	1720 (67-23/32)
152.4 (6)	NC38	NC38	121 (4-3/4)	550 (21-21/32)	50 (1-31/32)	300 (11-13/16)	18 或 30	1600 (63)