

磨铣鞋 Mill Shoes



磨铣鞋按其结构分为平底型、凹底型、梨型、锥型、领眼型、套铣型。其磨削表面堆焊有自砺作用的颗粒状耐磨材料或镶嵌硬质合金柱，用来磨碎诸如螺栓、螺母、牙轮、卡瓦牙、深井泵配件等井下落物及修整落鱼。

Milling shoes according to its structure is divided into flat type, concave bottom type, pear type, conical, pilot type, milling type. The grinding surface welding the granule wear-resisting material or inlaid with hard alloy column, used to grind, such as bolts, nuts, cone, slip teeth, deep well pump accessories and down hole fallings and trim the fish.

规格 Specifications

公称外径 D (mm)	接头螺纹 Connect	适用井眼直径 (mm) Well diameter
89	NC26、2-3/8REG	95.2 ~ 101.6
97		107.9 ~ 114.3
110	NC31 2-7/8REG 3-1/2REG	117.5 ~ 127.0
121		130.0 ~ 139.7
130		142.9 ~ 152.4
140	NC38 3-1/2REG 4-1/2REG	155.6 ~ 165.1
156		168.0 ~ 187.3
178		190.5 ~ 209.5
200	NC50 4-1/2REG	212.7 ~ 241.3
232		244.5 ~ 269.9
257	6-5/8REG	273.0 ~ 295.3
279		298.5 ~ 317.5
295		320.6 ~ 346.1
330		349.3 ~ 406.4
381		406.4 ~ 444.5
406	7-5/8REG	431.8 ~ 508
432		457.2 ~ 533.4
534		558.8 ~ 650
686		711.2 ~ 863.6